

SDS MAX SPEEDUSTER

10 CUT

No more dust!

A masonry drill with the power of rapid dust removal via its vacuum cleaning connecting sleeve. Excellent for drilling in spaces that needs a clean environment e.g. hospitals or laboratories.

Clean holes also aids easier and stronger fastening.

Size Range: 14–35mm Length: 610mm

**100% Carbide Head**  
With self centring 10 cutters for heavy duty drilling (22–35mm)

**2 Wide Suction Holes**  
For fast dust extraction

**SDS Max Shank**  
Suits ALL SDS Max rotary hammer drills

**Vacuum cleaner connecting sleeves**  
Suit 35mm diameter vacuum tubes

Sizes 14–20mm features a 3-cut head





SDS PLUS STOP DRILL

Stop Drills – for drop in anchors

Designed for use with drop in anchors. Featuring an integrated depth stop to accurately control the required drilling depth allowing fast, high-volume installation. Key applications include suspended electrical and ventilation systems, fixed-location seating and bollards.

Size Range: 8, 10, 12 and 15mm Length: 110–160mm

**3 Cutting Edges**  
135° self centring tip with three cutting edges guarantees a perfectly round hole

**Combination Spiral Flute**  
Half-round spiral accelerates dust extraction away from tip  
Square spiral combines compression channel with a depression chamber for perfectly controlled dust removal

**Depth Stop**  
Integrated depth stop for or accurate hole depth







**Sand-blasted Finish**  
Environmentally friendly production method with zero heavy metals

**SDS Plus Shank**  
Suits ALL SDS Plus rotary hammer drills





MASONRY DRILLS SELECTION CHART

	MASONRY	REO	REO PRO	REO EXTREME	SPEEDUSTER	STOP DRILL
	SDS PLUS	SDS PLUS	SDS PLUS / SDS MAX	SDS MAX	SDS MAX	SDS PLUS
						
Size Range	5-25mm	5-20mm	6-20mm	12-45mm	14-35mm	8-15mm
Length	110-410mm	110-460mm	160-460mm	340-920mm	610mm	110-160mm
Masonry	●	●	●	●		●
Reinforced Concrete		●	●	●	●	
Compressed Fibre Cement	●	●	●	●		●
Cement Sheet	●	●	●	●		●
Hebel	●	●	●	●		●
Brick	●	●	●	●	●	●
Stone	●	●	●	●	●	●
Granite	○	●	●	●		●
Marble		○	○	●		○

○ Effective ● Optimal



The PGM standard (PGM stands for "Prüfgemeinschaft Mauerbohrer" – drill bit testing) is the only guarantee of a perfect geometry for the precise drilling and preferred setting of your anchor studs. It is recommended to use only drill bits with this marking for anchor fixings to prevent accidents and liability cases.

www.suttontools.com



suttontools  
world class cutting tools

LARGEST MASONRY RANGE



## SDS PLUS 2-CUT MASONRY DRILL RANGE **2CUT**

### 30% faster

Combines hi-tech design with speed and efficiency. The innovative double milled combination spiral flute accelerate the removal of drill waste. The patented *Destructor* carbide tip is honed for greater accuracy and aggressive percussion effect, resulting in this drill being 30% faster than comparable products.

**Size range:** 5–25mm **Length:** 110–1000mm



## SDS PLUS 4-CUT REO DRILL RANGE **4CUT**

### Drills reinforced concrete

For reinforced concrete, brick, aerated concrete, stone and granite.

**Size range:** 6–20mm **Length:** 110–460mm



## SDS PLUS / SDS MAX 3-CUT REO PRO DRILL RANGE **3CUT**

### Professional choice for drilling reinforced concrete

Unique 3-Cut SDS Plus drill is the all concrete solution for professionals. Its sturdiness gives a life expectancy which is better than traditional drills. Combining powerful impact force with incursion and efficiency on concrete and reinforced concrete.

**Size range:** 5–20mm **Length:** 110–540mm



## SDS MAX 10-CUT REO EXTREME DRILL RANGE **10CUT**

### Superior performance in reinforced concrete

100% Carbide Head with 10-Cut head for increase speed and robust performance for 100's of holes in reinforced concrete.

- 6 Front Cutters - Elliptic 130° angle for better penetration
- 4 Side Cutters - Concentricity and accurate dimensions
- 6 Side Stabilisers -Hammering efforts focus on the drilling axis

**Size range:** 12–45mm **Length:** 340–1500mm

